

DIMENSIONS

Collection	PULSE CLICK+	
Width	209 mm	
Length	1494 mm	
Number of panels per pack	6 Panels	
m ² per pack	1,873 m ²	
Weight per pack	17,16 kg	
Density	1500±50 kg/m ³	
Total thickness	ISO24346	6,0 mm
Top layer	ISO24340	0,55 mm
Finishing	Advanced PU -Top coating with scratch & Stain Guard technologie	
Tongue and groove	Uniclic connection	

FACTORY WARRANTY

Usage class	EN ISO 10874 classification // ISO 20326	Class 33	
CE	EN 14041	DOP: QRHC 0501	
Warranty	Residential use	See warranty conditions	25 years
	Commercial use	See warranty conditions	5 years - on request up to 15 years

GENERAL DATA

	METHOD	PARAMETERS	NORM REQUIREMENTS	QUICK-STEP VALUES
Wear resistance	EN13329 - Annex E		≥2000 cycles	OK
Impact resistance	EN13329 - Annex F		≥1600 mm	≥1600 mm
Scratch resistance	EN16094		≤ MSR-A2 ≤ MSR-B2	MSR-A1 MSR-B2
Castor chairs	EN 425	25000 cycles	No delamination, no disturbance	OK
Displacement of furniture feet	EN 424	Foot 0,1 mm / 32 kg		No visible damage
Residual indentation	EN ISO 24343-1		≤0,1mm	≤0,1 mm
Resistance against staining	EN 438-2	Acetone - Coffee -NaOH -H2O2 - Shoe Polish		grade 5 No change
Swelling	ISO 24336		≤18%	no swelling
Locking strength	ISO 24334	Fmax long side Fmax short side	>1,0 kN/m >1,5 kN/m	>2 kN/m >3 kN/m
Dimensional stability	ISO 23999	6 hrs at 80°C	≤ 0,15 % shrinkage expansion Cupping	≤0,15% ≤0,15% <1mm
Fire classification	AS/ISO 9239.1 - 2003			9,4 Kw/m ² 111%min
UV resistance	ISO 105 B02	Blue reference	Class >6	Class 8
Slip resistance	AS 4586:2013			P4
Thermal resistance	EN 12667			0,016 m ² K/W

Floor heating Appropriate for all standard heating systems IN cement flooring. NOT appropriate for heating films and alternatives. Max contact temp ≤ 27°C. See separate installation instructions.

ENVIRONMENT & CERTIFICATES

AFFSET			A+
Formaldehyde emission	EN 14041:2004/AC:05+06	No added formaldehyde in production	<detection limit
TVOC 28 days	ISO16000 part 9-6	AgBB requirement after 28 days <1000 µg/m ³	<20µg/m ³
Content	Heavy metals+ lead/cadmium		NOT present
DANGEROUS SUBSTANCES	Carcinogenic, mutagenic or reprotoxic substances class 1A and 1B (candidate list)		NOT present
REACH	Regulation (EC) No 1907/2006		Compliant
Plasticizer	Ortho-phthalate free plasticizer		
Recycled content	Only INTERNAL recycled material used		

