



COLOURED KIT

Technical data sheet
English

General information

This elastic, acrylic-based paste is the ideal solution to fill gaps between skirtings and walls. Also suitable for gaps that can't be finished with skirtings, profiles or pipe covers. Available in matching colours.



Coloured Kit

Order code	QSKIT(-)
Packaging	Cartridge
Contents	310 ml
Colour	Available in 14 colours
Basis	Acrylic dispersion
Viscosity	Paste
Consumption	1 tube for +/- 15 m

Coloured Kit

Shelf life At least **24 months** in unopened packaging in a dry storage place at temperatures between 5°C and 25°C. Protect against frost.

Cure time Skin formation: +/- 20 min.

VOC emission < 1 %
(Volatile Organic Compound)

Application temperature 5 °C - 30 °C

Temperature resistance -20 °C - 80 °C (for fully cured product)

Applicable for:

- Gaps with a maximum expansion of 15 %.
- Do not use in combination with Vinyl Flex Click when the floor surface is larger than 10 m². For rooms smaller than 10 m², make sure to install an expansion profile in the doorway that connects this room with other rooms.
- Do not use in applications where continuous water contact is possible.

Safety

✓ **Eye protection**

Avoid contact with your eyes.

✓ **Skin protection**

Avoid contact with your skin. May cause an allergic reaction.

Features

Quick-Step accessories are specifically developed for Quick-Step floors.

✓ **Paintable**

✓ **Permanent elasticity**


Limited expansion is still possible.

✓ **Unique range of colours**

14 wood and stone-like colours specifically developed to match Quick-Step floors.

✓ **Matching table available**

Consult the best match for each Quick-Step floor in the sales organiser or on the website.



Installation

1. Work on a clean, dry, dust-free and grease-free surface.
2. Cut the nozzle of the Coloured kit at an angle to leave at least a 5 mm / 0.2 inch diameter opening. Apply the kit with a manual or pneumatic caulking gun into the gap. Be sure to avoid filling necessary dilatation gaps.
3. Moisten a spatula or your finger in a soap solution (water with detergent) and smoothen the kit.
4. Repeat the above steps in case of shrinking.
5. Quick-Step Coloured kit can be painted after 3 hours.
 - Fix the rail to the wall with screws or with Quick-Step One4All Glue

Maintenance

1. Before curing:
Coloured kit can be removed with a damp cloth or with cleaning wipes.
2. When cured:
Excess product should be removed mechanically with e.g. a plastic spatula. Then clean with cleaning wipes. For stubborn stains use a natural solvent spray.